

Specification Sheet: Ultra Violet LED Chip


Model: UC4020L20-A1

1) Optical and Electrical Characteristics (Ta=25°C)

Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	VF1	If=120mA	3.2	3.4	3.6	V
Reverse Current	Ir	Vr=-5V	-	-	10	uA
Peak Wavelength	WP	If=120mA	395		405	nm
Optical Power	IV	If=120mA	Refer to Rank Information			mW


2) Rank Information (Bin Table)

Po (Optical Power)			
BIN	Min	Typ.	Max.
65	65	-	70
70	70	-	75
75	75	-	80
80	80	-	85



3) Description

Description	Dimension	Material
Chip Size	980um x 480 um ± 30um	
Emission Area	960um x 460 um ± 30um	GaN Based Material
Chip Thickness	140 um ±20um	
P Bonding Pad	Φ100um ± 15um	Au
N Bonding Pad	Φ100um ± 15um	Au
Backside	Reflective layers	DBR



4) Caution

- Don't look directly into the LED light. UV radiation can harm your eyes.
- To prevent even inadequate exposure, wear protective eyewear.
- If LEDs are embedded in devices, please indicate warning labels against the UV light LED used.
- LED chips are very sensitive to static and surge. All equipment and human bodies must be properly grounded.
- LED chips should be stored at normal temperature (15 ~ 35°C) and humidity(45 ~ 70%). LED chips can be stored for maximum 3 months.



Soft-Epi Inc.

[H.Q.] 633-2, Goan-ri, Baekam-myeon, Cheoin-gu, Yongin-city, Gyeonggi, 449-863, Korea
 TEL : 82-31-330-7961,
 [R&D] 240 Opo-ro, Opo-eup, Gwangju-si, Gyeonggi-do, Korea
 Tel : +82-70-4915-5500, Fax : +82-31-765-3586
 URL: www.soft-epi.com